

Northwest Regional Office CLEAN WATER PROGRAM

Application Type Renewal
Facility Type Municipal
Major / Minor Major

NPDES PERMIT FACT SHEET INDIVIDUAL SEWAGE

 Application No.
 PA0028428

 APS ID
 932282

 Authorization ID
 1167573

	Applicant and	Facility Information	
Applicant Name	Brockway Area Sewer Authority	Facility Name	Brockway Area WWTP
Applicant Address	501 Main Street	Facility Address	70 Industrial Park Road
	Brockway, PA 15824	<u></u>	Brockway, PA 15824
Applicant Contact	Laurie Wayne, Manager	Facility Contact	Rick Boleen, Operator
Applicant Phone	(814) 268-6565	Facility Phone	(814) 265-0830
Client ID	202231	Site ID	263008
Ch 94 Load Status	Not Overloaded	Municipality	Brockway Borough
Connection Status	No Limitations	County	Jefferson
Date Application Rece	eived January 24, 2017	EPA Waived?	No
Date Application Acce	epted February,6, 2017	If No, Reason	Major Facility

Summary of Review

Supporting documents:



Brockway Area SA DO modeling.p...



Brockway Area SA texts medel...



Brockway Area SA Tentes Screen...



Brockway Teades Explanation(Ld...



Brockway Area SA DMR Summary.x...



Approve	Deny	Signatures				
X		ROBERT P. HUTCHINSON	DRAFT			
^		PERMITS SECTION	FINAL			
X		JUSTIN C. DICKEY, P.E.	DRAFT			
		ENVIRONMENTAL ENGINEER MANAGER	FINAL			
V		JOHN A. HOLDEN, P.E.				
X		REGIONAL PROGRAM MANAGER				

Outfall No. 001			Design Flow (MGD)	1.5
Latitude 41°	15' 08"		Longitude	-78° 47' 53"
Quad Name _Fa	alls Cree	k	Quad Code	04081
Wastewater Descr	ription:	Treated domestic sewag (except from shale gas e	e, industrial wastewater and oil a extraction activities)	nd gas brine wastewater
Receiving Waters	Little	Toby Creek	Stream Code	49666
NHD Com ID	13439	96185	RMI	10.62 mi
Drainage Area	90.2 r	ni ²	Yield (cfs/mi²)	0.102
Q ₇₋₁₀ Flow (cfs)	9.2		Q ₇₋₁₀ Basis	W. Br. Clarion R @ Wilcox gage
Elevation (ft)	1430		Slope (ft/ft)	0.00209
Watershed No.	_17-A		Chapter 93 Class.	CWF
Existing Use			Existing Use Qualifier	
Exceptions to Use	None		Exceptions to Criteria	None
Assessment Statu	s	Impaired		
Cause(s) of Impair	rment	Metals, Suspended Solid	ds, pH	
Source(s) of Impa	irment	Abandoned Mine Draina	ge	
TMDL Status		Final	Name Little Toby C	Creek
Background/Ambie	ent Data		Data Source	
pH (SU)		5.21	Mean value from the 6/09 L. 7	Toby Ck TMDL report
Temperature (°C)		20	Default temp for a CWF strea	m
Hardness (mg/L)		136	Applicant measured value rep	orted in the NPDES app.
CBOD ₅ (mg/L)		2	Default value	
NH ₃ -N (mg/L)		0.1	Default value	
Nearest Downstre	am Publi	c Water Supply Intake	PA American Water Co.	
PWS Waters	Clarion I		Flow at Intake (cfs)	195.14
PWS RMI	33.6 mi		Distance from Outfall	approx. 66 mi

Changes Since Last Permit Issuance: None

	Treatment Facility Summary							
Treatment Facility Na	ame: Brockway Area WWTP							
WQM Permit No.	Issuance Date							
3303403	5/6/04							
	Degree of			Avg Annual				
Waste Type	Treatment	Process Type	Disinfection	Flow (MGD)				
Sewage	Secondary w/ Ammonia Reduction	Oxidation Ditch	Ultraviolet					
Hydraulic Capacity	Organic Capacity			Biosolids				
(MGD)	(lbs/day)	Load Status	Biosolids Treatment	Use/Disposal				
1.5	2502	Not Overloaded	Aerobic Digestion	Land Application				

Changes Since Last Permit Issuance: None

WQM #3303403: Influent Pump Station, Screening, Bypass Bar Screen (manual), (2) Aerated Stormwater Storage Basins, (2) Oxidation Ditches, (2) Spiroflo Final Clarifiers, Ultraviolet Disinfection, Post-Aeration, an Aerobic Digester and a Belt Filter Press. The collection system for the service area was also constructed under this permit.

A 6/20/14 request was made to remove the plant's existing, manually operated trash basket screening assembly and replace it with an automatically controlled, powered mechanical screen. This was considered a minot WQM amendment and was therefore approved via e-mail on 7/14/14.

WQM #3316402 [issued 4/10/17]: Collection system improvements and a sewer service extension consisting of:

- North 219 vacuum pump station upgrade
- New, Circle Drive pump station
- Bond Street sewer replacement
- Keystone Road sewer extension

Development of Effluent Limitations					
6 46 H.N.		D : 51 (MOD)			
Outfall No.	001	Design Flow (MGD)	1.5		
Latitude	41° 15' 08"	Longitude	-78° 47' 53"		
		Treated domestic sewage, industrial wastewater and oil are from shale gas extraction activities)	nd gas brine wastewater (except		

Technology-Based Limitations

The following technology-based limitations apply, subject to water quality analysis and BPJ where applicable:

Pollutant	Limit (mg/l)	SBC	Federal Regulation	State Regulation
CBOD ₅	25	Average Monthly	133.102(a)(4)(i)	92a.47(a)(1)
CBOD5	40	Average Weekly	133.102(a)(4)(ii)	92a.47(a)(2)
	30	Average Monthly	133.102(b)(1)	92a.47(a)(1)
Total Suspended Solids	45	Average Weekly	133.102(b)(2)	92a.47(a)(2)
pH	6.0 – 9.0 S.U.	Min – Max	133.102(c)	95.2(1)
Fecal Coliform				
(5/1 - 9/30)	200 / 100 ml	Geo Mean	-	92a.47(a)(4)
Fecal Coliform				
(5/1 – 9/30)	1,000 / 100 ml	IMAX	-	92a.47(a)(4)
Fecal Coliform				
(10/1 – 4/30)	2,000 / 100 ml	Geo Mean	-	92a.47(a)(5)
Fecal Coliform				
(10/1 – 4/30)	10,000 / 100 ml	IMAX	-	92a.47(a)(5)
Total Residual Chlorine	0.5	Average Monthly	-	92a.48(b)(2)

Comments: The facility employs UV disinfection instead of chlorine.

Water Quality-Based Limitations

A "Reasonable Potential Analysis" determined the following parameters require water quality based limits (modeling output files attached):

Parameter	Parameter Limit (mg/l)		Model
NH ₃ -N (5/1-10/31)	16	Average Monthly	WQM 7.0 D.O./NH₃-N toxicity model
Selenium	0.025	Average Monthly	PENTOXSD toxics model
Chronic WET – c. dubia			
(survival & reproduction)	5.0 TUc	Daily Maximum	WET Testing Evaluation

Best Professional Judgment (BPJ) Limitations

Parameter	Limit (mg/l)	SBC	Basis
NH ₃ -N (5/1-10/31)	6.5	Average Monthly	Previous permit's limit being retained
NH ₃ -N (11/1-4/30)	19.5	Average Monthly	Previous permit's limit being retained
TDS	13,149 lb/day	Average Monthly	Grandfathered Amount - Chap 95.10(a)
TDS	28,683 lb/day	Daily Max	Grandfathered Amount - Chap 95.10(a)
Dissolved Oxygen	4.0	Min	SOP
Total Nitrogen	Monitor & Report	Average Monthly	SOP
Total Phosphorus	Monitor & Report	Average Monthly	SOP
UV light intensity	Monitor & Report (µw/cm²)	Average Monthly	SOP
BOD5 influent	Monitor & Report (conc. & mass)	Average Monthly	SOP
TSS influent	Monitor & Report (conc. & mass)	Average Monthly	SOP

Whole Effluent Toxicity (WET)

For (Outfall 001, Acute Chronic WET Testing was completed:
	For the permit renewal application (4 tests). Quarterly throughout the permit term. Quarterly throughout the permit term and a TIE/TRE was conducted
	Other:

The dilution series used for the tests was: 100%, 56.6%, 32%, 16%, and 10%. The Target Instream Waste Concentration (TIWC) to be used for analysis of the results is: 18%.

Summary of Four Most Recent Test Results

(NOTE - Enter results into one table, depending on which data analysis method was used).

NOEC/LC50 Data Analysis

	Ceriodapl	nnia Results (% E	Pimephale				
	NOEC	NOEC		NOEC	NOEC		
Test Date	Survival	Reproduction	LC50	Survival	Growth	LC50	Pass? *
2/2-9/16	100%	56.6%		100%	100%		Υ
5/3-10/16	100%	56.6%		100%	100%		Υ
7/31-8/5/16	56.6%	<10%		100%	100%		N
11/1-8/16	100%	32%		100%	100%		Υ

^{*} A "passing" result is that which is greater than or equal to the TIWC value.

Is there reasonable potential for an excursion above water quality standards based on the results of these tests? (*NOTE* – *In general, reasonable potential is determined anytime there is at least one test failure in the previous four tests*).

Evaluation of Test Type, IWC and Dilution Series for Renewed Permit

Acute Partial Mix Factor (PMFa): 0.45 Chronic Partial Mix Factor (PMFc): 1

1. Determine IWC - Acute (IWCa):

$$(Q_d \times 1.547) / ((Q_{7-10} \times PMFa) + (Q_d \times 1.547))$$

$$[(1.5 \text{ MGD x } 1.547) / ((9.2 \text{ cfs x } 0.45) + (1.5 \text{ MGD x } 1.547))] \times 100 = 36\%$$

Type of Test for Permit Renewal: Chronic

2. Determine Target IWCc (If Chronic Tests Required)

$$(Q_d \times 1.547) / (Q_{7-10} \times PMFc) + (Q_d \times 1.547)$$

TIWCc =
$$[(1.5 \text{ MGD} \times 1.547) / ((9.2 \text{ cfs} \times 1) + (1.5 \text{ MGD} \times 1.547))] \times 100 = 20\%$$

3. Determine Dilution Series

(NOTE - check Attachment C of WET SOP for dilution series based on TIWCa or TIWCc, whichever applies).

Dilution Series = 100%, 60%, 20%, 10%, and 5%.

WET Limits

Has reasonable potential been determined? \boxtimes YES \square NO

If WET limits will be established, identify the species and the limit values for the permit (TU).

Ceriodaphnia – TUc = 5 [= 1/TIWCc]

Proposed Effluent Limitations and Monitoring Requirements

The limitations and monitoring requirements specified below are proposed for the draft permit, and reflect the most stringent limitations amongst technology, water quality and BPJ. Instantaneous Maximum (IMAX) limits are determined using multipliers of 2 (conventional pollutants) or 2.5 (toxic pollutants). Sample frequencies and types are derived from the "NPDES Permit Writer's Manual" (362-0400-001), SOPs and/or BPJ.

Outfall 001, Effective Period: Permit Effective Date through Permit Expiration Date.

			Effluent L	imitations			Monitoring Re	quirements
Parameter	Mass Units	(lbs/day) (1)		Concentrati	ions (mg/L)		Minimum (2)	Required
Parameter	Average Monthly	Weekly Average	Minimum	Average Monthly	Weekly Average	Instant. Maximum	Measurement Frequency	Sample Type
Flow (MGD)	Report	Report Daily Max	XXX	XXX	XXX	XXX	Continuous	Measured
pH (S.U.)	XXX	XXX	6.0	XXX	9.0 Max	XXX	1/day	Grab
DO	XXX	XXX	4.0 Inst Min	XXX	XXX	XXX	1/day	Grab
CBOD5	250	375	XXX	20	30	40	2/week	24-Hr Composite
BOD5 Raw Sewage Influent	Report	XXX	XXX	Report	XXX	XXX	2/week	24-Hr Composite
TSS Raw Sewage Influent	Report	XXX	XXX	Report	XXX	XXX	2/week	24-Hr Composite
TSS	375	562	XXX	30	45	60	2/week	24-Hr Composite
Total Dissolved Solids	17574	29143 Daily Max	XXX	4274	XXX	7960	2/month	24-Hr Composite
Osmotic Pressure (mOs/kg)	XXX	XXX	XXX	Report	XXX	XXX	2/month	24-Hr Composite
Fecal Coliform (No./100 ml) Oct 1 - Apr 30	XXX	XXX	XXX	2000 Geo Mean	XXX	10000	2/week	Grab
Fecal Coliform (No./100 ml) May 1 - Sep 30	XXX	XXX	XXX	200 Geo Mean	XXX	1000	2/week	Grab
UV Intensity (μw/cm²)	XXX	XXX	XXX	Report	XXX	XXX	1/day	Measured
Total Nitrogen	XXX	XXX	XXX	Report	XXX	XXX	2/week	24-Hr Composite

Outfall 001, Continued (from Permit Effective Date through Permit Expiration Date)

Parameter	Effluent Limitations						Monitoring Requirements	
	Mass Units (lbs/day) (1)		Concentrations (mg/L)				Minimum (2)	Required
	Average Monthly	Weekly Average	Minimum	Average Monthly	Weekly Average	Instant. Maximum	Measurement Frequency	Sample Type
Ammonia								24-Hr
Nov 1 - Apr 30	243	XXX	XXX	19.5	XXX	39	2/week	Composite
Ammonia								24-Hr
May 1 - Oct 31	81	XXX	XXX	6.5	XXX	13	2/week	Composite
								24-Hr
Total Phosphorus	XXX	XXX	XXX	Report	XXX	XXX	2/week	Composite
								24-Hr
Total Barium	XXX	XXX	XXX	Report	XXX	XXX	2/month	Composite
				Report				24-Hr
Total Strontium	XXX	XXX	XXX	Avg Qrtly	XXX	XXX	1/quarter	Composite
				Report				24-Hr
Total Uranium (µg/L)	XXX	XXX	XXX	Avg Qrtly	XXX	XXX	1/quarter	Composite
				Report				24-Hr
Chloride	XXX	XXX	XXX	Avg Qrtly	XXX	XXX	1/quarter	Composite
				Report				24-Hr
Bromide	XXX	XXX	XXX	Avg Qrtly	XXX	XXX	1/quarter	Composite
				Report				24-Hr
Gross Alpha (pCi/L)	XXX	XXX	XXX	Avg Qrtly	XXX	XXX	1/quarter	Composite
				Report				24-Hr
Ra-226/228, Total (pCi/L)	XXX	XXX	XXX	Avg Qrtly	XXX	XXX	1/quarter	Composite
Chronic WET - Ceriodaphnia				5.0				
Survival (TUc)	XXX	XXX	XXX	Daily Max	XXX	XXX	1/quarter	See Permit
Chronic WET - Ceriodaphnia				5.0				
Reproduction (TUc)	XXX	XXX	XXX	Daily Max	XXX	XXX	1/quarter	See Permit
								24-Hr
Selenium, Total (Interim)*	Report	XXX	XXX	Report	XXX	XXX	2/month	Composite
	0.04	V0.07	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\		2007		., .	24-Hr
Selenium, Total (Final)**	0.31	XXX	XXX	0.025	XXX	0.062	1/week	Composite

^{*} Interim limits apply from the permit effective date (PED) to 3 years after the PED. ** Final limits apply from 3 years after the PED to the expiration date.

Compliance Sampling Location: Outfall 001 – after disinfection

Special Conditions:

- Toxics Reduction Evaluation for Selenium
- Whole Effluent Toxicity testing with a TU limit
- Solids Handling/Reporting
- Hauled-In Waste restrictions
- Limit on the quantity of wastewater associated with natural gas drilling
- Receipt of Drilling Waste Volume restriction

Comments: The previous permit's special condition related to the development and submittal of a Radiation Protection Plan is no longer applicable since the applicant has completed this requirement. The condition's language was removed from this permit.

The CBOD₅ limit was adjusted to conform to the Regional practice of expressing the limits in multiples of 5 mg/l. This changes the monthly average limit from 19 mg/l to 20 mg/l. The new limit is protective of water quality since modeling shows the limit could be the secondary treatment level of 25 mg/l. To be consistent with the previous permit(s0, seasonal limits were not included for this parameter.

This permit also relaxes the monitoring frequency of the indicator pollutants associated with natural gas-related wastewater. Monitoring for these parameters will change from 2/month to 1/quarter. This is based on a review of the past 3 years of data collected on these parameters. The monitoring reduction does not include Barium and Osmotic Pressure.

Tools and References Used to Develop Permit

WQM for Windows Model (see Attachment)

PENTOXSD for Windows Model (see Attachment)

Toxics Screening Analysis Spreadsheet (see Attachment)

Determining Water Quality-Based Effluent Limits, 391-2000-003, 12/97.

Implementation Guidance Design Conditions, 391-2000-006, 9/97.

Technical Reference Guide (TRG) WQM 7.0 for Windows, Wasteload Allocation Program for Dissolved Oxygen and Ammonia Nitrogen, Version 1.0, 391-2000-007, 6/2004.

Interim Method for the Sampling and Analysis of Osmotic Pressure on Streams, Brines, and Industrial Discharges, 391-2000-008, 10/1997.

Technical Reference Guide (TRG) PENTOXSD for Windows, PA Single Discharge Wasteload Allocation Program for Toxics, Version 2.0, 391-2000-011, 5/2004.

Implementation Guidance for Section 93.7 Ammonia Criteria, 391-2000-013, 11/97.

Implementation Guidance for Application of Section 93.5(e) for Potable Water Supply Protection Total Dissolved Solids, Nitrite-Nitrate, Non-Priority Pollutant Phenolics and Fluorides, 391-2000-019, 10/97.

Implementation Guidance for the Determination and Use of Background/Ambient Water Quality in the Determination of Wasteload Allocations and NPDES Effluent Limitations for Toxic Substances, 391-2000-022, 3/1999.

SOP: Establishing Effluent Limitations for Individual Sewage Permits

SOP: New & Reissuance Sewage Individual NPDES Permit Applications